

# Aalto Trade Exterior Semi Gloss

Product	Aalto Trade Exterior Semi Gloss AT301	
Description	Aalto Trade Exterior Semi Gloss is a professional quality waterbased paint in a semi gloss finish for exterior surfaces. Provides exceptional performance on most common exterior substrates, including weatherboards, timber, concrete and galvanised iron.	
Guarantee	Aalto Trade Exterior Semi Gloss comes with a 10 year guarantee. For details, visit <a href="http://www.aaltopaint.co.nz">www.aaltopaint.co.nz</a>	
Typical Uses	May be used on suitably prepared: <ul style="list-style-type: none"> <li>- Weatherboards</li> <li>- Timber</li> <li>- HardieFlex™</li> <li>- Concrete and concrete blocks</li> <li>- Textured surfaces</li> <li>- Galvanised iron, Colorsteel®</li> <li>- Fibre cement products</li> </ul>	
Physical Properties	Binder type	100% acrylic
	Solvent	Water
	Colour	White and tinted colours
	Finish	Semi gloss – 35% gloss
	Dry time	30 minutes at 20°C
	Recoat time	2 hours at 20°C
	Number of coats	2
	Theoretical coverage	10-12m <sup>2</sup> per litre
	Rec. film thickness	100 microns per coat, WFT
	Thinning and clean up	Water
Preparation	Ensure surfaces are free from loose and flaking paint. Wash surfaces with a suitable exterior cleaner prior to painting to remove dirt, oils, grease and other contaminants. Where there has been mould, treat the area with a moss and mould remover.	
Application	<p>Aalto Trade Exterior Semi Gloss can be applied by synthetic brush, roller, or spray. Airless spray – a 415 or 417 tip is recommended for weatherboards, and a 517 tip is recommended for textured surfaces before being back-rolled.</p> <p>Weatherboards – pre-primed</p> <ol style="list-style-type: none"> <li>1. Apply 2 coats of Aalto Trade Exterior Semi Gloss, allowing 2 hours between coats</li> </ol> <p>New timber</p> <ol style="list-style-type: none"> <li>1. Apply 1 coat of Aalto 3 in 1 Undercoat</li> <li>2. Apply 2 coats of Aalto Trade Exterior Semi Gloss, allowing 2 hours between coats</li> </ol> <p>Repaints</p> <ol style="list-style-type: none"> <li>1. Sand existing paint work and spot prime bare timber with Aalto 3 in 1 Undercoat</li> <li>2. Apply 2 coats of Aalto Trade Exterior Semi Gloss, allowing 2 hours between coats</li> </ol>	



**Concrete block, reinforced concrete**

1. Where porous, seal with Aalto 3 in 1 Undercoat thinned 50% with water
2. Apply 1 coat of Aalto 3 in 1 Undercoat unthinned
3. Apply 2 coats of Aalto Trade Exterior Semi Gloss, allowing 2 hours between coats

**Fibre cement**

1. Seal with Aalto Trade Exterior Semi Gloss thinned 20% with water
2. Apply 2 coats of Aalto Trade Exterior Semi Gloss, allowing 2 hours between coats

**Galvanised iron**

1. Treat rusty areas with an appropriate preparation solution
2. Apply 1 coat of Procoat Oil Based Galvanised Iron Primer
3. Apply 2 coats of Aalto Trade Exterior Semi Gloss, allowing 2 hours between coats

**Maintenance**

Maintain your exterior paint surface by washing it every 12 months (after each winter is a great time), with a suitable exterior cleaner to remove dirt deposits. We do not recommend the use of bleach as this can affect the appearance of the colour over time. Dirt, salt, and bird deposits left on the paint surface will encourage the growth of mould, and affect the paints performance.

**Performance and Limitations****Performance**

- Excellent durability and gloss retention
- Excellent intercoat adhesion
- Excellent flexibility
- Resists dirt pick-up

**Limitations**

- Should not be applied if temperatures are below 10°C or when it is liable to drop below 10°C during the drying period
- Dry time may be impeded if the relative humidity is high
- Should not be used on closing surfaces around doors and windows

**Health and Safety**

For detailed health and safety information refer to Material Safety Datasheet (MSDS)

**Usage**

- Provide adequate ventilation during use
- Keep out of reach of children

**Personal**

- Avoid contact with skin and eyes
- Wash hands after use

**Protective equipment**

- Wear protective eyewear and waterproof gloves
- When spraying, wear dust mask or suitable respirator

**Storage**

- Store away from direct sunlight

**Health Effects**

If poisoning occurs, contact a doctor or Poisons Information Centre (NZ 0800 764 766).  
If swallowed: Rinse mouth with water. Do NOT induce vomiting. Give a glass of water.  
Eyes: If in eyes, hold eyes open, flush with running water for at least 15 minutes,  
Skin: If skin contact occurs, remove contaminated clothing and wash skin thoroughly.  
Inhaled: Remove from contaminated area.

# aalto

**Spills and Disposal**

Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local council regarding the disposal of empty paint containers. Empty paint containers should be left open in a well-ventilated area to dry out. When dry, recycle steel containers via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may vary between local authorities.

# aalto