

# Aalto Ultra Premium Exterior Satin

Product	Aalto Ultra Premium Exterior Satin AA307	
Description	Aalto Ultra Premium Exterior Satin is a premium waterbased and self priming paint for exterior surfaces. This reinforced acrylic paint has been formulated to provide a washable and UV resistant finish to common exterior substrates including weatherboards, timber, concrete and galvanised iron.	
Guarantee	Aalto Ultra Premium Exterior Satin paint comes with a 15 year guarantee. For details, visit <a href="http://www.aaltopaint.co.nz">www.aaltopaint.co.nz</a>	
Typical Uses	May be used on suitably prepared: <ul style="list-style-type: none"> <li>- Weatherboards</li> <li>- Colorsteel®</li> <li>- Timber</li> <li>- HardieFlex™</li> <li>- Plywood</li> <li>- Galvanised iron</li> <li>- Steel</li> <li>- Fibre cement products</li> <li>- Concrete and concrete blocks</li> <li>- Zinalume®</li> </ul>	
Physical Properties	Binder type Solvent Colour Finish Dry time Recoat time Number of coats Theoretical coverage Rec. film thickness Thinning and clean up	100% acrylic Water White and tinted colours Satin – 20% gloss 30 minutes at 20°C 2 hours at 20°C 2 or 3 (see application details below) 12-14m <sup>2</sup> per litre 100 microns per coat, WFT Water
Preparation	Ensure surfaces are free from loose and flaking paint. Wash surfaces with a suitable exterior cleaner prior to painting to remove dirt, oils, grease and other contaminants. Where there has been mould, treat the area with a moss and mould remover.	
Application	Aalto Ultra Premium Exterior Satin can be applied by synthetic brush, roller, or spray. Airless spray – a 415 or 417 tip is recommended for weatherboards and smooth surfaces, and a 517 tip is recommended for textured surfaces, followed by back rolling.	
	Weatherboards (pre-primed) <ol style="list-style-type: none"> <li>1. Apply 2 coats of Aalto Ultra Premium Exterior Satin, allowing 2 hours between coats</li> </ol>	
	New timber <ol style="list-style-type: none"> <li>1. Apply 1 coat of Aalto 3 in 1 Undercoat, allow 2 hours to dry</li> <li>2. Apply 2 coats of Aalto Ultra Premium Exterior Satin, allowing 2 hours between coats</li> </ol>	



**Repaints**

1. Sand existing paint work and spot prime bare timber with Aalto 3 in 1 Undercoat
2. Apply 2 coats of Aalto Ultra Premium Exterior Satin, allowing 2 hours between coats

**Concrete block**

1. Where porous, seal with Aalto 3 in 1 Undercoat thinned 50% with water
2. Apply 1 coat of Aalto 3 in 1 Undercoat, unthinned, allow 2 hours to dry
3. Apply 2 coats of Aalto Ultra Premium Exterior Satin, allowing 2 hours between coats

**Fibre cement, concrete slab, concrete tiles, bricks**

1. Seal with 1 coat of Aalto 3 in 1 Undercoat
2. Apply 2 coats of Aalto Ultra Premium Exterior Satin, allowing 2 hours between coats

**Galvanised iron**

1. Treat any areas of rust with an appropriate preparation solution
2. Apply 1 coat of Procoat Oil Based Galvanised Iron Primer
3. Apply 2 coats of Aalto Ultra Premium Exterior Satin, allowing 2 hours between coats

**Maintenance**

Maintain your exterior paint surface by washing it every 12 months (after each winter is a great time), with a suitable exterior cleaner to remove dirt deposits. We do not recommend the use of bleach as this can affect the appearance of the colour over time. Dirt, salt, and bird deposits left on the paint surface will encourage the growth of mould, and affect the paints performance.

**Performance and Limitations****Performance**

- Excellent durability and gloss retention
- Exceptional intercoat adhesion
- Excellent flexibility
- Resists dirt pick-up
- Suitable for use on surfaces used for the collection of drinking water

**Limitations**

- When applying over cedar or highly treated timber where severe stain bleeding may occur, seal with Aalto 3 in 1 Undercoat before applying 2 coats of Aalto Ultra Premium Exterior
- Should not be used on closing surfaces around doors and windows
- Should not be applied if temperatures are below 5°C or when it is liable to drop below 5°C during the drying period
- Dry time may be impeded if the relative humidity is high

**Health and Safety**

For detailed health and safety information refer to Material Safety Datasheet (MSDS)

**Usage**

- Provide adequate ventilation during use
- Keep out of reach of children

**Personal**

- Avoid contact with skin and eyes
- Wash hands after use

**Protective equipment**

- Wear protective eyewear and waterproof gloves
- When spraying, wear dust mask or suitable respirator

**Storage**

- Store away from direct sunlight

# aalto

**Health Effects**

If poisoning occurs, contact a doctor or Poisons Information Centre (NZ 0800 764 766).  
If swallowed: Rinse mouth with water. Do NOT induce vomiting. Give a glass of water.  
Eyes: If in eyes, hold eyes open, flush with running water for at least 15 minutes,  
Skin: If skin contact occurs, remove contaminated clothing and wash skin thoroughly.  
Inhaled: Remove from contaminated area.

**Spills and Disposal**

Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local council regarding the disposal of empty paint containers. Empty paint containers should be left open in a well-ventilated area to dry out. When dry, recycle steel containers via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may vary between local authorities.

# aalto