

## Aalto Ultra Premium Interior Low Sheen

|                     |   |                               |
|---------------------|---|-------------------------------|
| Product             | Aalto Ultra Premium Interior Low Sheen<br>AA332   |                               |
| Description         | Aalto Ultra Premium Interior Low Sheen is a premium waterbased paint in a low sheen finish for interior walls and ceilings. This reinforced acrylic paint has been formulated to provide a beautiful matt appearance while delivering a washable finish with excellent stain resistant properties.  |                               |
| Guarantee           | Aalto Ultra Premium Interior Low Sheen comes with a 15 year guarantee.<br>For details, visit <a href="http://www.aaltopaint.co.nz">www.aaltopaint.co.nz</a>   |                               |
| Typical Uses        | May be used on suitably prepared: <ul style="list-style-type: none"><li>- Plasterboard</li><li>- Wallboard, Gib® board</li><li>- Timber</li><li>- Fibrolite</li><li>- HardieFlex™</li><li>- Customwood</li></ul>  |                               |
| Physical Properties | Binder type   | Reinforced acrylic            |
|                     | Solvent   | Water                         |
|                     | Colour  | White and tinted colours      |
|                     | Finish  | Low sheen – 5% gloss          |
|                     | Dry time  | 1 hour at 20°C                |
|                     | Recoat time   | 2 hours at 20°C               |
|                     | Number of coats   | 2                             |
|                     | Theoretical coverage  | 10-12m <sup>2</sup> per litre |
|                     | Rec. film thickness   | 100 microns per coat, WFT     |
|                     | Thinning and clean up   | Water                         |
| Preparation         | Ensure surfaces are free from loose and flaking paint. Wash surfaces with a suitable cleaner such as sugar soap prior to painting to remove dirt, oils, grease and other contaminants. Where there has been mould, treat the area with a moss and mould remover.  |                               |
| Application         | Aalto Ultra Premium Interior Low Sheen can be applied by synthetic brush, roller, or spray.<br>Airless spray – a 415 or 515 tip is recommended. When spraying, Aalto Ultra Premium Interior Low Sheen will require thinning to suit.<br>Rolling – a synthetic 8mm nap roller sleeve is recommended.<br><br>Plasterboard, wallboard, Gib® board <ol style="list-style-type: none"><li>1. Apply 1 coat of Aalto Interior Sealer Undercoat</li><li>2. Apply 2 coats of Aalto Ultra Premium Interior Low Sheen, allowing 2 hours between coats</li></ol><br>Timber, fibrolite, HardieFlex™, customwood <ol style="list-style-type: none"><li>1. Apply 1 coat of Aalto 3 in 1 Undercoat</li><li>2. Apply 2 coats of Aalto Ultra Premium Interior Low Sheen, allowing 2 hours between coats</li></ol> |                               |
| Maintenance         | Maintain your interior paint finish by cleaning with a damp cloth and neutral detergent (such as diluted sugar soap). Cleaners that contain solvents may affect the surface appearance and the paints longevity. Dry dust corners frequently to avoid dust and dirt build up.   |                               |

# aalto

**Performance and  
Limitations****Performance**

- Excellent washability
- Exceptional coverage and opacity
- Easy to apply
- Excellent stain resistance

**Limitations**

- Should not be applied if temperatures are below 10°C or when it is liable to drop below 10°C during the drying period
- Dry time may be impeded if the relative humidity is high
- Should not be used on closing surfaces of doors or window frames, or on areas subject to pressure
- Full stain resistance may take up to 7 days to develop

**Health and Safety**

For detailed health and safety information refer to Material Safety Datasheet (MSDS)

**Usage**

- Provide adequate ventilation during use
- Keep out of reach of children

**Personal**

- Avoid contact with skin and eyes
- Wash hands after use

**Protective equipment**

- Wear protective eyewear and waterproof gloves
- When spraying, wear dust mask or suitable respirator

**Storage**

- Store away from direct sunlight

**Health Effects**

If poisoning occurs, contact a doctor or Poisons Information Centre (NZ 0800 764 766).

If swallowed: Rinse mouth with water. Do NOT induce vomiting. Give a glass of water.

Eyes: If in eyes, hold eyes open, flush with running water for at least 15 minutes,

Skin: If skin contact occurs, remove contaminated clothing and wash skin thoroughly.

Inhaled: Remove from contaminated area.

**Spills and Disposal**

Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local council regarding the disposal of empty paint containers. Empty paint containers should be left open in a well-ventilated area to dry out. When dry, recycle steel containers via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may vary between local authorities.

# aalto