Aalto Ultra Premium Waterbased Enamel Low Sheen

A durable and hard-wearing finish for interior walls. Aalto Ultra Premium Waterbased Enamel Low Sheen is a premium waterbased enamel in a low sheen finish for interior walls and ceilings. Formulated to provide a beautiful eggshell appearance while delivering a completely washable finish with superior stain-resistant properties.

General Information

Product name and identifier	Aalto Ultra Premium Waterbased Enamel Low Sheen **AA336**
Guarantee	15 year guarantee Aalto Group guarantees that Aalto Ultra Premium Waterbased Enamel Low Sheen will provide a serviceable finish for 15 years, provided it is applied on properly prepared surfaces, as per label and technical data sheet (TDS) instructions. For full details of this guarantee, visit aalto.co.nz
Typical uses	Ideal for use on interior walls, ceilings and trim
Features and benefits	• Available in the full Aalto colour palette • Washable with most common household cleaners • Anti-mould additives make it perfect for wet areas • Excellent coverage and opacity • Easy to apply • Excellent stain resistance • Non-yellowing • Low odour and low VOC (<60g/L)

Certifications

Eco® Choice Aotearoa

License No. 0724193

NEW ZEALAND MADE®

License No. 801793

For more details of these certifications, visit aalto.co.nz. View the full range of Aalto Eco Choice accredited products here

Precautions and Limitations

Limitations	• Should not be applied when temperatures are below 10°C or when liable to drop below 10°C during the drying period • Dry time may be impeded if the relative humidity is high • After application, allow 12–48 hours before the area becomes fully serviceable, with full hardness developing after 2–3 weeks • Not recommended for exterior applications
Tinted colours	Check colour before application. Ensure paint is stirred thoroughly before use.

aalto

Physical Properties

Binder type	Unique cross-linking acrylic	**Solvent**	Water
Colour	White + full Aalto base system Available in a wide range of tinted colours	**Finish**	Low sheen / 5% gloss @ 60°
Dry time	Touch dry 1 hour at 20°C Recoat in 4 hours at 20°C	**Number of coats**	2 *Dark or bright colours may require 3 coats*
Coverage	10-12m^2 per litre	**Recommended film thickness**	100 microns per coat, WFT
Thinning and clean up	Water (in hot conditions, can be thinned up to 5% with hot weather thinners)		

Preparation

Ensure surfaces are clean, dry, and free from dirt, dust and any other contaminants prior to paint application.

Previously painted surfaces	Ensure surfaces are free from loose and flaking paint. Wash surfaces with a suitable cleaner such as sugar soap prior to painting to remove dirt, oils, grease and other contaminants. Where there has been mould, treat the area with a moss and mould remover. Spot prime where required with Aalto Ultra Premium 3 in 1 Undercoat [*TDS363*] If painting over old oil based enamels, sand to a uniform dull finish and apply 1 full coat of Aalto Ultra Premium 3 in 1 Undercoat [*TDS363*]
Bare timber	Sand if required to a smooth finish. Dust off well. Apply 1 coat of Aalto Ultra Premium 3 in 1 Undercoat [*TDS363*] or Aalto Tradeline Primer Sealer Undercoat [*TDS428*]
Bare fibrous plaster, plaster, Gib® board, wallboard	Wipe down well to remove any surface dust. Apply 1 coat Aalto Tradeline Sealer Undercoat [*TDS366*]
Particle board, customwood	Apply 1 coat of Aalto Ultra Premium 3 in 1 Undercoat [*TDS363*]
PVC, Formica, Melteca, Laminex®	Lightly sand the surface. Wash well with sugar soap, rinse and allow to dry. Apply 1 coat of Aalto Ultra Premium 3 in 1 Undercoat [*TDS363*]

Application

Aalto Ultra Premium Waterbased Enamel Low Sheen can be applied by synthetic brush, roller, or spray.

Airless spray	A 412 or 413 tip is recommended. Aalto Ultra Premium Waterbased Enamel Low Sheen may be thinned up to 5% with clean, fresh water.
Rolling	An 8–10mm microfibre or Dacron roller sleeve is recommended for smooth surfaces. For textured surfaces, use a 15mm microfibre sleeve. After application to each area, back-roll in one direction to ensure an even gloss finish.

Apply 2 coats of Aalto Ultra Premium Waterbased Enamel Low Sheen, allowing 4 hours between coats

Maintenance

Clean with a damp cloth and neutral detergent (such as diluted sugar soap). Cleaners that contain solvents may affect the surface appearance and the paints longevity. Dry dust corners frequently to avoid dust and dirt build up.

Health and Safety

Safety Data Sheet	SDS334-2025.3
Safety information	• Keep out of reach of children • If medical advice is needed, have product container/label to hand • Avoid contact with skin and eyes, wear personal protective equipment as below • Wash hands after use
Personal equipment	Wear eye protection and gloves. When spraying, wear a suitable mask or respirator.
Storage	Store sealed in original container. Store out of direct sunlight.
Spills and disposal	Do not allow any spilt paint to enter waterways. Absorb spills with sand or other inert material. Do not pour any leftover paint down drains. Check with your local paint authority or council for any paint recycling schemes in your area. Alternatively, brush out any unwanted paint onto newspaper, allow to dry then place into domestic waste. Dry empty containers in a well-ventilated area, then recycle via your local recycling facility.

In case of emergency, phone CHEMWATCH EMERGECY (24/7) 0800 700 112 or NZ POISONS 0800 764 766

© Copyright Aalto Group Ltd. 2026

Disclaimer: Any information provided in this data sheet is provided in good faith and is correct at the time of publication. Application details are based on generic scenarios, for any specific application details please contact your Aalto paint specialist.

Products and coating systems can be expected to perform as stated in this data sheet, provided the substrate is in good condition, preparation is completed to a high standard, and application is carried out by a suitably experienced/skilled applicator.

Application of the correct colour is the responsibility of the applicator.