Aalto Tradeline Easy Sand Sealer

Aalto Tradeline Easy Sand Sealer Undercoat is a professional quality waterbased sealer undercoat for interior broadwall surfaces. Formulated to provide a smooth, even finish with easy sand properties and excellent opacity.

General Information

Product name and identifier	Aalto Tradeline Easy Sand Sealer *AT365*
Typical uses	May be used on suitable interior surfaces, including: • Wallboard, plasterboard, Gib® board • Plaster
Features and benefits	• Excellent spray application • Free sanding to a smooth finish • Fast drying • Excellent holdout for topcoats

Certifications

Eco® Choice Aotearoa

License No. 0724193

NEW ZEALAND MADE

License No. 801793

For more details of these certifications, visit aalto.co.nz. View the full range of Aalto Eco Choice accredited products here

Precautions and Limitations

Limitations	• Not recommended for use on timber surfaces • For wet areas, we recommend Procoat by Aalto Pigmented Sealer (solvent based) for superior adhesion • Should not be applied when temperatures are below 10°C or when liable to drop below 10°C during the drying period • Dry time may be impeded if the relative humidity is high

Physical Properties

Binder type	Copolymer acrylic	**Solvent**	Water
Colour	White	**Finish**	Matt
Dry time	Touch dry 30 minutes at 20°C Recoat in 2 hours at 20°C	**Number of coats**	1
Coverage	8–10m^2 per litre	**Recommended film thickness**	100 microns per coat, WFT
Thinning and clean up	Water		

Preparation

Ensure surfaces are clean, dry, and free from dirt, dust and any other contaminants prior to application. Stir thoroughly using a broad flat paddle and an up and down scooping motion.

Application

Aalto Tradeline Easy Sand Sealer can be applied by synthetic brush, roller, or spray.

Airless spray	A 417 or 517 tip is recommended. Thinning is not recommended.
Rolling	A 10mm microfibre or Dacron roller sleeve is recommended.

Bare wallboard, plaster board, Gib® board	Ensure that the surface is sound and free from weak, powdery, or under cured stoppings. Remove any excess stopping compounds. Avoid sanding the paper surface as this will cause furring, leading to textural differences in the finish. Apply 1 coat of Aalto Tradeline Easy Sand Sealer. Lightly sand and dust off well.

Health and Safety

Safety Data Sheet	SDS365-2023.2 Link to SDS
Safety information	• Keep out of reach of children • Avoid contact with skin and eyes, wear personal protective equipment as below • Avoid breathing spray, vapours • Wash hands after use
Personal equipment	Wear eye protection and gloves. When spraying, wear a suitable mask or respirator.
Storage	Store sealed in original container. Store out of direct sunlight.

Spills and disposal	Do not allow any spilt paint to enter waterways. Absorb spills with sand or other inert material. Do not pour any leftover paint down drains. Check with your local paint authority or council for any paint recycling schemes in your area. Alternatively, brush out any unwanted paint onto newspaper, allow to dry then place into domestic waste. Dry empty containers in a well-ventilated area, then recycle via your local recycling facility.

In case of emergency, phone CHEMWATCH EMERGECY (24/7) 0800 700 112 or NZ POISONS 0800 764 766

Copyright Aalto Group Ltd. 2026

Disclaimer: Any information provided in this data sheet is provided in good faith and is correct at the time of publication. Application details are based on generic scenarios, for any specific application details please contact your Aalto paint specialist.

Products and coating systems can be expected to perform as stated in this data sheet, provided the substrate is in good condition, preparation is completed to a high standard, and application is carried out by a suitably experienced/skilled applicator.