

Aalto Tradeline Easy Sand Sealer Undercoat

Product	Aalto Tradeline Easy Sand Sealer Undercoat AT365	
Description	Aalto Tradeline Easy Sand Sealer Undercoat is a professional quality waterbased sealer undercoat for interior broadwall surfaces. Formulated to provide a smooth, even finish with easy sand properties and excellent opacity.	
Guarantee	Aalto Tradeline Easy Sand Sealer Undercoat comes with a 10 year guarantee. For details, visit www.aaltopaint.co.nz	
Typical Uses	May be used on suitably prepared: <ul style="list-style-type: none">- New Gib® board- Plaster	
Physical Properties	Binder type	Copolymer acrylic
	Solvent	Water
	Colour	White
	Finish	Matt
	Dry time	30 minutes at 20°C
	Recoat time	2 hours at 20°C
	Number of coats	1
	Theoretical coverage	8-10m ² per litre
	Rec. film thickness	100 microns per coat, WFT
	Thinning and clean up	Water
Preparation	Ensure surfaces are free from loose and flaking paint. Wash surfaces with a suitable interior cleaner such as sugar soap prior to painting to remove dirt, oils, grease and other contaminants. Where there has been mould, treat the area with a moss and mould remover.	
Application	Aalto Easy Sand Sealer Undercoat can be applied by synthetic brush, roller, or spray. Airless spray – a 417 or 517 tip is recommended. Interior Gib® board and plasterboard <ol style="list-style-type: none">1. Apply 1 coat Aalto Easy Sand Sealer Undercoat2. Lightly sand and dust off3. Apply 2 coats of topcoat	
Maintenance	Maintain your interior paint finish by cleaning with a damp cloth and neutral detergent (such as diluted sugar soap). Cleaners that contain solvents may affect the surface appearance and the paints longevity. Dry dust corners frequently to avoid dust and dirt build up.	
Performance and Limitations	Performance	<ul style="list-style-type: none">- Excellent spray application- Free sanding to a smooth finish- Excellent holdout for topcoats

aalto

Limitations

- Should not be applied if temperatures are below 10°C or when it is liable to drop below 10°C during the drying period
- Dry time may be impeded if the relative humidity is high
- For improved adhesion to timber substrates, we recommend Aalto 3 in 1 Undercoat

Health and Safety

For detailed health and safety information refer to Material Safety Datasheet (MSDS)

Usage

- Provide adequate ventilation during use
- Keep out of reach of children

Personal

- Avoid contact with skin and eyes
- Wash hands after use

Protective equipment

- Wear protective eyewear and waterproof gloves
- When spraying, wear dust mask or suitable respirator

Storage

- Store away from direct sunlight

Health Effects

If poisoning occurs, contact a doctor or Poisons Information Centre (NZ 0800 764 766).

If swallowed: Rinse mouth with water. Do NOT induce vomiting. Give a glass of water.

Eyes: If in eyes, hold eyes open, flush with running water for at least 15 minutes,

Skin: If skin contact occurs, remove contaminated clothing and wash skin thoroughly.

Inhaled: Remove from contaminated area.

Spills and Disposal

Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local council regarding the disposal of empty paint containers. Empty paint containers should be left open in a well-ventilated area to dry out. When dry, recycle steel containers via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may vary between local authorities.

aalto