

Aalto Ultimate Interior Matt

The ultimate interior paint, with a silky matt finish that showcases your chosen Aalto colour beautifully. Utilising the latest technologies, Aalto Ultimate Interior Matt is suitable for all areas of the home, including kitchens and bathrooms. Highly washable and super tough, and enhanced with anti-bacterial and anti-mould additives, it's our most advanced paint yet. Low VOC and low odour, and ideal for all interior walls, ceilings and trims.

General Information

Product name and identifier	Aalto Ultimate Interior Matt AA738
Guarantee	25 year guarantee Aalto Group guarantees that Aalto Ultimate Interior Matt will provide a serviceable finish for 25 years, provided it is applied on properly prepared surfaces, as per label and technical data sheet (TDS) instructions. For full details of this guarantee, visit aalto.co.nz
Typical uses	Ideal for use on interior walls, ceilings and trim
Features and benefits	• Available in the full Aalto colour palette • Exceptional washability and scrub resistance • Anti-bacterial and anti-mould additives make it perfect for wet areas • Excellent coverage and opacity • Easy to apply • Excellent stain resistance • Suitable for all interior painting applications • Low odour and low VOC (<50g/L)

Certifications



License No. 0724193



License No. 801793

For more details of these certifications, visit aalto.co.nz. View the full range of Aalto Eco Choice accredited products [here](#)

Precautions and Limitations

Limitations	• Should not be applied when temperatures are below 10°C or when liable to drop below 10°C during the drying period • Dry time may be impeded if the relative humidity is high • Full hardness and stain resistance may take up to 7 days to develop
Tinted colours	Check colour before application. Ensure paint is stirred thoroughly before use.

The Aalto logo, consisting of the word "aalto" in a bold, blue, lowercase sans-serif font, oriented vertically.

Physical Properties

Binder type	Acrylic emulsion	Solvent	Water
Colour	White + full Aalto base system Available in a wide range of tinted colours	Finish	Matt / 2% gloss @ 60°
Dry time	Touch dry 1 hour at 20°C Recoat in 2 hours at 20°C	Number of coats	2
Coverage	10-12m ² per litre	Recommended film thickness	100 microns per coat, WFT
Thinning and clean up	Water (in hot conditions, can be thinned up to 5% with hot weather thinners)		

Preparation

Ensure surfaces are clean, dry, and free from dirt, dust and any other contaminants prior to paint application.

Previously painted surfaces	Ensure surfaces are free from loose and flaking paint. Wash surfaces with a suitable cleaner such as sugar soap prior to painting to remove dirt, oils, grease and other contaminants. Where there has been mould, treat the area with a moss and mould remover. Spot prime where required with Aalto Ultra Premium 3 in 1 Undercoat [TDS363] If painting over old oil based enamels, sand to a uniform dull finish and apply 1 full coat of Aalto Ultra Premium 3 in 1 Undercoat [TDS363]
Bare timber	Sand if required to a smooth finish. Dust off well. Apply 1 coat of Aalto Ultra Premium 3 in 1 Undercoat [TDS363] or Aalto Tradeline Primer Sealer Undercoat [TDS428]
Bare fibrous plaster, plaster, Gib® board, wallboard	Wipe down well to remove any surface dust. Apply 1 coat Aalto Tradeline Sealer Undercoat [TDS366]
Particle board, customwood	Apply 1 coat of Aalto Ultra Premium 3 in 1 Undercoat [TDS363]

Application

Aalto Ultimate Interior Matt can be applied by synthetic brush, roller, or spray.

Airless spray	A 415 or 515 tip is recommended. Aalto Ultimate Interior Matt may be thinned up to 5% with clean, fresh water. We recommend back-rolling in one direction after spraying to achieve a consistent finish.
Rolling	An 8–10mm microfibre or Dacron roller sleeve is recommended for smooth surfaces. For textured surfaces, use a 15mm microfibre sleeve. After application to each area, back-roll in one direction to ensure a consistent matt finish.

Apply 2 coats of Aalto Ultimate Interior Matt, allowing 4 hours between coats

aalto

Maintenance

Clean with a damp cloth and neutral detergent (such as diluted sugar soap). Cleaners that contain solvents may affect the surface appearance and the paint's longevity. Dry dust corners frequently to avoid dust and dirt build up.

Health and Safety

Safety Data Sheet	SDS738-2025.2
Safety information	• Keep out of reach of children • If medical advice is needed, have product container/label to hand • Do not breathe vapors, spray • Avoid contact with skin and eyes, wear personal protective equipment as below • Wash hands after use
Personal equipment	Wear eye protection and gloves. When spraying, wear a suitable mask or respirator.
Storage	Store sealed in original container. Store out of direct sunlight.
Spills and disposal	Do not allow any spilt paint to enter waterways. Absorb spills with sand or other inert material. Do not pour any leftover paint down drains. Check with your local paint authority or council for any paint recycling schemes in your area. Alternatively, brush out any unwanted paint onto newspaper, allow to dry then place into domestic waste. Dry empty containers in a well-ventilated area, then recycle via your local recycling facility.

In case of emergency, phone CHEMWATCH EMERGENCY (24/7) 0800 700 112 or NZ POISONS 0800 764 766

© Copyright Aalto Group Ltd. 2026

Disclaimer: Any information provided in this data sheet is provided in good faith and is correct at the time of publication. Application details are based on generic scenarios, for any specific application details please contact your Aalto paint specialist.

Products and coating systems can be expected to perform as stated in this data sheet, provided the substrate is in good condition, preparation is completed to a high standard, and application is carried out by a suitably experienced/skilled applicator.

Application of the correct colour is the responsibility of the applicator.