

procoat

Roof Paint

WITH ADVANCED 4TH GENERATION ACRYLIC TECHNOLOGY
Provides superior adhesion, weather protection and durability



Proudly made in NZ, designed for superior performance
in NZ conditions

by aalto

Aalto Group Ltd.
7 Akatea Road, Glendene, Auckland 0602
p: 0800 761 333 w: aalto.co.nz

A premium roof paint, designed for superior performance on NZ roofs

Procoat Roof Paint is a premium waterbased and self-priming paint in a satin finish for all common roof substrates, including galvanised iron, Colorsteel® and concrete tiles.

Made specifically for the unique New Zealand weather conditions, Procoat Roof Paint provides superior adhesion and maximum protection with anti-corrosive properties, and is suitable for use on roofs used for the collection of drinking water.

Protects from UV and
resists colour fade

Easy application –
brush, roller or spray

Waterbased,
self-priming formula

15 year guarantee




Available in 12 standard colours




Ebony




Flaxpod



Ironsand



Karaka



Grey Friars



New Denim Blue



Permanent Green



Mist Green



Lignite



Pioneer Red



Sandstone Grey



Titania



The colours on this chart are representations only. Due to limitations in the printing process, these may not represent the true colour.

Preparation

To achieve the best results, ensure the surface is dry, free from dirt, dust and other contaminants. Wash surfaces with Procoat Roof Clean, especially where moss and mould is present.

Procoat Roof Clean

Procoat Roof Clean Concentrate is a high strength cleaner designed to treat and remove moss, mould, algae and lichen from most common exterior surfaces, including roofs. Procoat Roof Clean contains a special blend of biodegradable surfactants to ensure maximum performance.



Application



Procoat Roof Paint can be applied by brush, roller or spray.

Coverage: 12-14m² per litre

Stir well before and during use with a broad flat paddle, using an up and down scooping motion.

On previously painted roofs, weathered Colorsteel®, concrete tiles:

1. Spot prime where required with Procoat Waterbased Galvanised Iron Primer
2. Apply 2 coats of Procoat Roof Paint

On new or lightly weathered galvanised iron:

1. Prime with 1 coat of Procoat Waterbased Galvanised Iron Primer or Procoat Roof Paint
2. Apply 2 coats of Procoat Roof Paint

On heavily weathered galvanised iron:

1. Prime with 1 coat of Procoat Waterbased Galvanised Iron Primer or Procoat Oil Based Galvanised Iron Primer if rust is present
2. Apply 2 coats of Procoat Roof Paint

Some roofs may require additional preparation prior to painting. For detailed preparation, application and maintenance details, refer to the product label or technical data sheet at www.aalto.co.nz If you are unsure of the best product to use for your project, consult with your local Procoat stockist for recommendations.

To extend the life of your coating we recommend washing every 12 months with Procoat Roof Clean or Procoat Exterior House & Deck Wash. This removes any surface contaminants and prevents the growth of moss and mould.

15 Year Guarantee

Aalto guarantee that Procoat Roof Paint will not blister, peel, or flake for 15 years provided it is applied and maintained as per label and technical data sheet instructions. This guarantee does not cover paint failure caused by any breakdown of previous coatings or substrates, or from mechanical damage. If Procoat Roof Paint does not perform to this guarantee, Aalto will provide paint free of charge to rectify the affected area/s.

All Procoat products are proudly made in NZ by Aalto Group. Aalto Group manufactures a trusted range of paints and coatings that provide a guaranteed, long lasting finish.

