

PROCOAT PREMIUM SATIN ENAMEL

Date of issue: 16 November 2021 NZ Safety Data Sheet

1. Identification of the Substance/Mixture and Supplier.









Product name:	Procoat premium satin enamel (342-100)
Application:	Surface coating
Company:	DECORA GROUP LTD 7 Akatea Road, Glendene, Auckland, New Zealand.
Telephone:	09 818 9215
Facsimile:	09 818 7862
Emergency telephone:	0800 761 333

2. Hazards Identification.

HSNO Status: Classified as hazardous according to the criteria of HSNO. HSNO approval number HSR002669

DG Status: Classified as Dangerous Goods according to NZS5433

Signal Word: DANGER

HAZARD CLASSIFICATIONS HSNO	HAZARD STATEMENTS	GHS Pictogram
Flammable liquid, category 3	H226 Flammable liquid and vapour.	
Aspiration hazard Category 1	H304 May be fatal if swallowed and enters airways.	
Eye irritation Category 2	H319 Causes serious eye irritation.	
Skin sensitisation Category 1	H317 May cause an allergic skin reaction.	
Carcinogenicity Category 2	H351 Suspected of causing cancer.	
Specific target organ toxicity – repeated exposure Category 1	H372 Causes damage to organs through prolonged or repeated exposure.	
Specific target organ toxicity – single exposure Category 3 narcotic effects	H336 May cause drowsiness or dizziness.	
Hazardous to the aquatic environment chronic Category 2	H411 Toxic to aquatic life with long lasting effects.	

PREVENTION STATEMENTS

P102	Keep out of reach of children.
P103	Read label before use.
P104	Read Safety Data Sheet before use.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.

PROCOAT PREMIUM SATIN ENAMEL

Date of issue: 16 November 2021 NZ Safety Data Sheet

P260	DO not breathe fume/gas/mist/vapours.	
P264	Wash hands thoroughly after handling.	
P270	Do not eat, drink or smoke when using this product.	
P271	Use only outdoors or in a well-ventilated area.	
P272	Contaminated work clothing should not be allowed out of the workplace.	
P273	Avoid release to the environment.	
P280	Wear protective gloves/protective clothing/eye protection/face protection.	
P281	Use personal protective equipment as required.	
RESPONSE STATEMENTS		
P101	If medical advice is needed, have product container or label at hand.	
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.	
P331	Do NOT induce vomiting.	
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P337+P313	If eye irritation persists: Get medical advice/ attention.	
P302+P352	IF ON SKIN: Wash with plenty of soap and water.	
P333+P313	If skin irritation occurs: Get medical advice/ attention.	
P363	Wash contaminated clothing before reuse.	
P308+P313	IF exposed or concerned: Get medical advice/ attention.	
P304+P340	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.	
P312	Call a POISON CENTER or doctor/physician if you feel unwell.	
P391	Collect spillage.	
P370+P378	In case of fire: Use foam, carbon dioxide or dry chemical powder for extinction.	
STORAGE STATEMENTS		
P403+P233	Store in a well-ventilated place. Keep container tightly closed.	
P403+P235	Store in a well-ventilated place. Keep cool.	
P405	Store locked up.	
DISPOSAL STATEMENTS		
P501	Refer to Section 13.	
3. Composition/Information on Ingredients.		
Chemical Entity	CAS Number	Proportion %w/w
Setal 270 EHV WS-70		30-40
White spirits hi flash		10-20
Troymax 2002 drier blend		<2
Tego color aid 7060		<1
Balance of ingredients: Non-hazardous, or below the hazardous threshold.		
4. First Aid Measures.		
Swallowed	If swallowed do NOT induce vomiting. Give water to drink. Get medical attention immediately.	
Inhaled	If inhaled, move the victim to fresh air immediately. Begin artificial respiration if breathing has stopped. Obtain medical attention if symptoms occur.	
Eye Contact	If splashed in the eyes, wash out immediately with water. Obtain medical attention immediately.	
Skin Contact	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Get medical attention if symptoms occur.	
Further Information	For advice contact the National Poisons Centre – 0800 POISON (0800 764 766) – or a doctor, immediately.	
5. Fire-Fighting Measures.		

PROCOAT PREMIUM SATIN ENAMEL

Date of issue: 16 November 2021 NZ Safety Data Sheet

Suitable extinguishing media	In case of fire, use water spray (fog), foam, dry chemical or CO ₂ .		
Unsuitable extinguishing media	High volume water jet.		
Hazards from the substance	In a fire or if heated, a pressure increase will occur and the container may burst.		
Hazardous combustion products	Decomposition products may include: Carbon oxides, Nitrogen oxides, Other noxious substances.		
Special precautions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.		
Special protective equipment for fire fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.		
6. Accidental Release Measures.			
Personal precautions	Wear appropriate Personal Protective Equipment (see section 8). Provide adequate ventilation.		
Environmental precautions	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).		
Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert dry material and place in an appropriate waste disposal container. Eliminate all ignition sources. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.		
Large spill	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Eliminate all ignition sources. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.		
7. Handling and Storage.			
Handling	Wear appropriate PPE, and ensure there is adequate ventilation and extraction in the work area. Avoid skin or eye contact, or breathing in the product. Follow precautions listed in section 2 for handling flammable/combustible liquids.		
Storage	Keep container dry and tightly closed, in a cool, well-ventilated area, away from direct sunlight. Keep away from heat, sparks and open flame.		
8. Exposure Control/Personal Protection			
Exposure Standards			
No exposure limits set for the finished product, listed components below.			
Product/Ingredient	WES/TWA	WES/STEL	Reference
Xylene (o-, m-, p- isomers)	50ppm/217mg/m ³		NZ-WES
Naphthalene	0.5ppm/2.6mg/m ³	2ppm/10mg/m ³	NZ-WES
Quartz ^f	-/0.05mg/m ³		NZ-WES
^f Quartz is only a problem as a respirable dust, once bound it is non hazardous.			
Engineering Controls	General ventilation and local exhaust should be suitable to keep vapour concentrations below WES/TWA. Ventilation equipment should be explosion-		

PROCOAT PREMIUM SATIN ENAMEL

Date of issue: 16 November 2021 NZ Safety Data Sheet

	proof when operating in flammable zones.
Personal Protection	
Respiratory	Wear a vapour respirator.
Eyes	Wear chemical goggles/face protection.
Hands	Wear chemical gloves – PVC, Polychloroprene or Nitrile.
Other	Wear overalls or dust coat. Use PVC apron when handling large quantities.



9. Physical and Chemical Properties

PROPERTY	SPECIFICATION
Appearance (physical state, colour, etc.)	Liquid, White
Odour	Not available
Odour threshold	Not available
pH	Not available
Melting point/freezing point	Not available
Initial boiling point and boiling range	Est. 147-199°C
Flash point	Est. 39°C
Flammability (solid, gas)	Not available
Upper/lower flammability or explosive limits	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	1.30-1.38
Solubility (ies)	Not available
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Kinematic viscosity	75-80

10. Stability and Reactivity

Stability	The product is stable
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	Fire, sparks, static electricity, heat, ignition sources.
Incompatible materials	Oxidising materials.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological Information

Original data sourced from CCID and RM SDSs	
Classification:	Aspiration Hazard – Category 1
Health Effects:	May be fatal if swallowed and enters airways.
Reference:	Determined by applying mixture rules.
Classification:	Eye Irritant – Category 2
Health Effects:	Causes serious eye irritation.
Reference:	Determined by applying mixture rules.

PROCOAT PREMIUM SATIN ENAMEL

Date of issue: 16 November 2021 NZ Safety Data Sheet

Classification:	Skin sensitisation Category 1
Health Effects:	May cause an allergic skin reaction
Reference:	Determined by applying mixture rules.
Classification:	Carcinogenicity Category 2
Health Effects:	Suspected of causing cancer.
Reference:	Determined by applying mixture rules.
Classification:	STOT-SE, Cat 3 (narcotic effects)
Health Effects:	May cause drowsiness or dizziness.
Reference:	Determined by applying mixture rules.
Classification:	STOT-RE – 6.9A
Health Effects:	Causes damage to organs through prolonged or repeated exposure.
Reference:	Determined by applying mixture rules.
Acute Oral Toxicity	Does not trigger HSNO classification
Acute Dermal Toxicity	Does not trigger HSNO classification
Acute Inhalation Toxicity	Does not trigger HSNO classification
Skin Irritancy/Corrosion	Does not trigger HSNO classification
Respiratory Sensitisation	Does not trigger HSNO classification
Mutagenic	Does not trigger HSNO classification
Reproductive/Development Toxicity	Does not trigger HSNO classification
Swallowed:	Not available
Inhaled:	Not available
Skin:	Not available
Eyes:	Not available
Chronic Effects:	Not available
Toxicity Data	
Product Acute Toxicity Estimate	
ORAL LD50	>2000 mg/kg
DERMAL LD50	>2000 mg/kg
INHALATION LC50 (vapours)	>20 mg/L/4H
INHALATION LC50 (dust/mist)	>5 mg/L/4H
12. Ecological Information	
This product is classified as Ecotoxic according to the criteria of HSNO.	
Ecotoxic Ingredients:	
Ingredient	Classification
Setal 270-EHV ES-70	Hazardous to the aquatic environment chronic Category 2
Tego Colour	Hazardous to the aquatic environment chronic Category 1, Hazardous to the aquatic environment acute Category 1
White spirits	Hazardous to the aquatic environment chronic Category 2



PROCOAT PREMIUM SATIN ENAMEL

Date of issue: 16 November 2021 NZ Safety Data Sheet

Troymax 2002 drier blend	Hazardous to the aquatic environment chronic Category 3
Product/Ingredient	Species, L(E)C50
	FISH
Naphthalene	LC50 (Bluegill): 31026µg/L/96h
Naphthalene	LC50 (Pink Salmon): 900µg/L/96h
Naphthalene	LC50 (Crimson Spotted rainbow trout): 315µg/L/96h
White spirits	Oncorhynchus mykiss: 10-30 mg/l/96h
	CRUSTACEAN
White spirits	EL50 (Daphnia magna): 10-22 mg/l/48h
Tego Colour	EC10(Daphnia magna, 21 d): 0,07 mg/INOEC(Daphnia magna, 21 d): 0,048 mg
	ALGAL
Naphthalene	EC50 (Green algae): 25000µg/L/7-8 days
White spirits	ErL50: 4.1 mg/l/72h(Pseudokirchneriella subcapitata)
Product/Ingredient:	
Persistence & Degradability	Not available
Mobility	Not available
Bioaccumulative Potential	Not available
Other	Not available
Product Calculated Aquatic Ecotoxicity – L(E)C50 mg/L:	
Hazardous to the aquatic environment chronic Category 2: >1 - ≤10	
Ecotoxicity Data – CCID – Not available	
Persistence & Degradability - Not available	
Mobility - Not available	
Bioaccumulation Potential - Not available	
Other - Not available	
13. Disposal Considerations.	
Do not let this product enter the environment. Do not dispose of in waterways or sewers. Dispose of this material and its container as hazardous waste, via a licensed facility. See local council for disposal/recycling information.	
14. Transportation Information.	
Regulated for transport	Keep separated from foodstuffs
UN Number:	1263
Proper Shipping Name:	PAINT (contains petroleum distillates)
Class:	3
Packing Group:	III
Hazchem:	3Y
Marine Pollutant:	Yes

PROCOAT PREMIUM SATIN ENAMEL

Date of issue: 16 November 2021 NZ Safety Data Sheet

Land/Sea/Air 	EHSM also required for Sea/Air 
15. Regulatory Information.	
Group Standard:	Surface Coatings and Colourants (Flammable, Carcinogenic) Group Standard 2020
HSNO Approval Number:	HSR002669
HSNO CONTROLS	
SDS required when any quantity is present in a workplace.	
At least 2 x 4.5kg powder fire extinguishers required when 500L is present in a workplace.	
Emergency Response Plan and Secondary Containment required when >1000L is present in a workplace	
Flammable signage required when >1000L is stored.	
Ecotoxic signage required when >1000L is stored.	
(Class Flammable Liquid, category 3) Hazardous Substances Location Compliance Certificate required for:	>500L (closed containers >5L) >1500L (closed containers up to 5L) >250L (open containers)
(Class Flammable Liquid, category 2/3 - 3.1B, 3.1C) Hazardous Atmosphere Zone required for:	>100L (closed containers) >25L (decanting) >5L (open occasionally) >1L (open containers in continuous use)
Certified Handler	Not Required
Tracking	Not Required
All ingredients are on the New Zealand Inventory of Chemicals (NZIoC), or exempt.	
Any existing national regulations on the handling of dangerous substances should be observed. Controls for hazardous substances are based upon current knowledge. Where multiple chemicals are stored, controls will need to take into account aggregate quantities. Contact a WorkSafe approved Compliance Certifier for further information and guidance.	
This material is not subject to the following agreements:	
<ul style="list-style-type: none"> • Montreal Protocol (Ozone Depleting Substances) • The Stockholm Convention (Persistent Organic Pollutants) • The Rotterdam Convention (Prior Informed Consent) 	
16. Other Information.	
HSNO = Hazardous Substances and New Organisms Act 1996. EPA = Environmental Protection Authority CCID = Chemical Classification and Information Database (EPA) NZ WES = New Zealand Work Exposure Standard TWA = Time Weighted Average STEL = Short Term Exposure Limit Date of SDS Preparation: 16 November 2021	

The data given here is based on current knowledge and experience. The purpose of this Safety Data Sheet is to describe products in terms of their safety requirements. The above details do not imply any guarantee concerning composition, properties or performance of the product.

PROCOAT PREMIUM SATIN ENAMEL

Date of issue: 16 November 2021 NZ Safety Data Sheet