

aaltopaint

SB Finish Coat

Enamel Gloss, Semi Gloss, Satin

Product Line Aalto SB Finish Coat
AS340-341-342

Description Aalto SB Finish Coat is an ultra premium oil based enamel paint in a gloss, semi gloss or satin finish for interior and exterior applications. Formulated to provide a hard wearing moisture resistant coating it is suitable for use over both waterbased and enamel undercoats.

Guarantee Aalto SB Finish Coat comes with a 10 year guarantee.
For details, visit www.aaltopaint.co.nz

Typical Uses May be used on suitably prepared:

- Weatherboards
- Timber
- Galvanised iron
- Gib® board
- Old painted surfaces
- Structural steel
- Customwood

Properties

| | |
|----------------------------|---|
| Binder type | Alkyd resin |
| Solvent | White spirits |
| Colour | White and tinted colours |
| Finish | Gloss: 80% gloss Semi Gloss: 35% gloss Satin: 20% gloss |
| Dry time | 4 hours at 20°C |
| Recoat time | 16 hours at 20°C |
| Number of coats | 2 |
| Theoretical coverage | 10-12m ² per litre |
| Recommended film thickness | 100 microns per coat WFT |
| Thinning/clean up | Mineral turpentine |

Preparation

Ensure surfaces are free from loose and flaking paint. Wash surfaces with a suitable cleaner such as sugar soap prior to painting to remove any oil, grease, dirt or other contaminants. Where there has been mould, treat with a mould remover.

Application

Aalto SB Finish Coat may be applied by brush, roller or spray.
Airless spray – a 409 or 411 tip is recommended.

Timber – exterior, pre-primed

1. Apply 1 coat of Aalto SB Oil Based Primer Undercoat, allow to dry overnight
2. Apply 2 coats of Aalto SB Finish Coat, allowing overnight drying between coats

New Timber – exterior

1. Apply 2 coats of Aalto SB Oil Based Primer Undercoat, allowing overnight drying between coats
2. Sand and thoroughly dust off to a smooth finish
3. Apply 2 coats of Aalto SB Finish Coat, allowing overnight drying between coats

New Timber – interior

1. Apply 1 coat of Aalto SB Oil Based Primer Undercoat or Aalto WB Trade 3 in 1 Undercoat, allow to dry overnight
2. Sand and thoroughly dust off to a smooth finish
3. Apply 2 coats of Aalto SB Finish Coat, allowing overnight drying between coats

Gib® Board

1. Apply 1 coat of Aalto WB Trade Interior Sealer Undercoat, allow 1 hour to dry
2. Apply 1 coat of Aalto SB Oil Based Primer Undercoat, allow to dry overnight
3. Apply 2 coats of Aalto SB Finish Coat, allowing overnight drying between coats

Weathered Galvanised Iron, Structural Steel

1. Apply 1 coat of Procoat Etch Primer, allow 2 hours to dry
2. Apply 2 coats of Aalto SB Finish Coat, allowing overnight drying between coats

Performance & Limitations

Performance

- Excellent gloss retention in exterior applications
- Can be used over Aalto WB Trade Sealer Undercoat and Aalto WB Trade 3 in 1 Undercoat

Limitations

- Due to poor alkali resistance, usage on cementitious substrates or brick work is not recommended
- When using on particle board, the wax content necessitates using Aalto WB Trade 3 in 1 Undercoat as a first coat
- Drying and appearance can be affected by application at low temperatures and high humidity

Health & Safety

For detailed health and safety information refer to material safety data sheet (MSDS).

Usage

- Provide adequate ventilation during use
- Keep out of reach of children

Personal

- Avoid contact with skin and eyes
- Wash hands after use

Protective Equipment

- Wear eye protection and waterproof gloves
- When spraying, wear dust mask or suitable respirator

Storage

- Store away from direct sunlight

Health Effects

If poisoning occurs, contact a Doctor or Poisons Information Centre (NZ 0800 764 766).

Swallowed: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water.

Eyes: If in eyes, hold eyes open, flush with running water for at least 15 minutes.

Skin: If skin contact occurs, remove contaminated clothing and wash skin thoroughly.

Inhaled: Remove from contaminated area.

Spills & Disposal

Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Do not pour leftover paint down the drain.

Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local Council regarding the disposal of empty paint containers. Empty paint containers should be left open in a well-ventilated area to dry out. When dry, recycle steel containers via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may vary between local authorities.