

aaltopaint

SB Undercoat

Oil Based Primer Undercoat

Product Line Aalto SB Oil Based Primer Undercoat
AS380

Description Aalto SB Oil Based Primer Undercoat is a premium all purpose oil based primer undercoat for interior and exterior applications. Formulated for quick drying to an easy to sand surface it is ideal as a first coat for bare timber, customwood and plywood.

Guarantee Aalto SB Oil Based Primer Undercoat comes with a 10 year guarantee. For details, visit www.aaltopaint.co.nz

Typical Uses May be used on suitably prepared:

- Weatherboards
- Timber
- Old painted surfaces
- Suitably prepared metals

Properties

Binder type	Alkyd resin
Solvent	Mineral turpentine
Colour	White
Finish	Matt
Dry time	4 hours at 20°C
Recoat time	16 hours at 20°C
Number of coats	1
Theoretical coverage	10-12m ² per litre
Recommended film thickness	80 microns per coat WFT
Thinning/clean up	Mineral turpentine

Preparation Ensure surfaces are free from loose and flaking paint. Wash surfaces with a suitable cleaner such as sugar soap prior to painting to remove any oil, grease, dirt or other contaminants. Where there has been mould, treat with a mould remover.

Application Aalto SB Oil Based Primer Undercoat may be applied by brush, roller or spray. Airless spray – a 415 or 515 tip is recommended.

All Surfaces

1. Apply 1 coat of Aalto SB Oil Based Primer Undercoat, allow to dry overnight
2. Apply 2 coats of selected topcoat

Performance & Limitations

Performance

- Formulated to give excellent holdout for enamel topcoats
- Good flow and sanding properties
- Excellent adhesion

Limitations

- Not recommended for cementitious substrates
- Needs to be overcoated within 4 weeks
- Poor alkali resistance

Health & Safety

For detailed health and safety information refer to material safety data sheet (MSDS).

Usage

- Provide adequate ventilation during use
- Keep out of reach of children

Personal

- Avoid contact with skin and eyes
- Wash hands after use

Protective Equipment

- Wear eye protection and waterproof gloves
- When spraying, wear dust mask or suitable respirator

Storage

- Store away from direct sunlight

Health Effects

If poisoning occurs, contact a Doctor or Poisons Information Centre (NZ 0800 764 766).

Swallowed: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water.

Eyes: If in eyes, hold eyes open, flush with running water for at least 15 minutes.

Skin: If skin contact occurs, remove contaminated clothing and wash skin thoroughly.

Inhaled: Remove from contaminated area.

Spills & Disposal

Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local Council regarding the disposal of empty paint containers. Empty paint containers should be left open in a well-ventilated area to dry out. When dry, recycle steel containers via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may vary between local authorities.