

# aaltopaint

## SB Undercoat Pigmented Sealer

**Product Line** Aalto SB Pigmented Sealer  
AS384

**Description** Aalto SB Pigmented Sealer is a premium quality oil based sealer designed for application on porous and loosely bound surfaces. Formulated to seal nicotine or water stained walls and ceilings prior to painting, and as a broadwall sealer prior to wallpapering.

**Guarantee** Aalto SB Pigmented Sealer comes with a 10 year guarantee.  
For details, visit [www.aaltopaint.co.nz](http://www.aaltopaint.co.nz)

**Typical Uses** May be used on suitably prepared:

- Gib® board
- Pinex
- Fibrous plaster
- As a wallboard sealer before wallpapering
- Brick and cementitious surfaces
- Timber

### Properties

Binder type	Urethane modified alkyd resin
Solvent	Mineral turpentine
Colour	White
Finish	Satin
Dry time	4 hours at 20°C
Recoat time	16 hours at 20°C
Number of coats	1
Theoretical coverage	8-10m <sup>2</sup> per litre
Recommended film thickness	80 microns per coat WFT
Thinning/clean up	Mineral turpentine

**Preparation** Ensure surfaces are free from loose and flaking paint. Wash surfaces with a suitable cleaner such as sugar soap prior to painting to remove any oil, grease, dirt or other contaminants. Where there has been mould, treat with a mould remover.

## Application

Aalto SB Pigmented Sealer may be applied by brush, roller or spray.  
Airless spray – a 415 or 515 tip is recommended.

### All Surfaces

1. Carefully sand to a smooth, even surface, dust off thoroughly
2. Apply 1 coat of Aalto SB Pigmented Sealer, allow to dry overnight
3. Apply 2 coats of selected topcoat

## Performance & Limitations

### Performance

- Excellent adhesion to alkyd and acrylic topcoats
- Easy to apply

### Limitations

- As a sealer, Aalto SB Pigmented Sealer is not designed to impart opacity
- Contains solvent

## Health & Safety

For detailed health and safety information refer to material safety data sheet (MSDS).

### Usage

- Provide adequate ventilation during use
- Keep out of reach of children

### Personal

- Avoid contact with skin and eyes
- Wash hands after use

### Protective Equipment

- Wear eye protection and waterproof gloves
- When spraying, wear dust mask or suitable respirator

### Storage

- Store away from direct sunlight

## Health Effects

If poisoning occurs, contact a Doctor or Poisons Information Centre (NZ 0800 764 766).

Swallowed: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water.

Eyes: If in eyes, hold eyes open, flush with running water for at least 15 minutes.

Skin: If skin contact occurs, remove contaminated clothing and wash skin thoroughly.

Inhaled: Remove from contaminated area.

## Spills & Disposal

Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local Council regarding the disposal of empty paint containers. Empty paint containers should be left open in a well-ventilated area to dry out. When dry, recycle steel containers via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may vary between local authorities.