

aaltopaint

WB Interior

Waterbased Enamel Flat

Product Line Aalto WB Interior Enamel Flat
AA338

Description Aalto WB Interior Enamel Flat is an ultra premium waterbased enamel in a flat finish for interior walls and ceilings. Formulated to provide a beautiful flat appearance while retaining washability and stain resistance.

Guarantee Aalto WB Interior Enamel Flat comes with a 15 year guarantee.
For details, visit www.aaltopaint.co.nz

Typical Uses May be used on suitably prepared:

- Interior walls where a flat, wipeable finish is desired
- Ceilings

Properties

Binder type	Unique cross-linking acrylic
Solvent	Water
Colour	White and tinted colours
Finish	Flat: >2% gloss
Dry time	1 hour at 20°C
Recoat time	2-4 hours at 20°C
Number of coats	2
Theoretical coverage	10-12m ² per litre
Recommended film thickness	100 microns per coat WFT
Thinning/clean up	Water

Preparation Ensure surfaces are free from loose and flaking paint. Wash surfaces with a suitable cleaner such as sugar soap prior to painting to remove any oil, grease, dirt or other contaminants. Where there are areas of mould, treat with a mould remover.

Old enamels will require fine sanding to a uniform dull finish.

Application

Aalto WB Interior Enamel Flat may be applied by synthetic brush, roller or spray.
Airless spray – a 415 or 515 tip is recommended.
Rolling – a synthetic 6-10mm nap roller sleeve is recommended.

Because of the quick drying nature of Aalto WB Interior Enamel Flat, in hot conditions it may be necessary to thin up to 5% with hot weather thinners.

When rolling walls that are highlighted by natural lighting from large windows, you will need to "lay-off" with the roller in one direction after applying the paint. This should be done in one continuous operation from one end of the wall to the other without stopping. For large areas two applicators may be required, one to lay on the paint and the other to "lay-off".

Timber, Particle Board, Customwood

1. Apply 1 coat of Aalto WB Trade 3 in 1 Undercoat, allow 2 hours to dry
2. Apply 2 coats of Aalto WB Interior Enamel Flat, allowing 2 hours between coats

Gib® Board, Fibrous Plaster

1. Apply 1 coat of Aalto WB Trade Sealer Undercoat, allow 2 hours to dry
2. Lightly sand and dust off
3. Apply 2 coats of Aalto WB Interior Enamel Flat, allowing 2 hours between coats

Previously Painted Surfaces

1. Remove any flaking paint off the surface and sand to a smooth finish
2. If painting over old oil based enamels, wash down with sugar soap and sand lightly to a dull finish
3. Prime any areas of bare timber with Aalto WB Trade 3 in 1 Undercoat
4. Apply 2 coats of Aalto WB Interior Enamel Flat, allowing 2 hours between coats

Performance & Limitations

Performance

- Ultimate hard wearing finish
- Can be used in place of traditional oil based enamels
- Non-yellowing
- Easy application properties with excellent flow and levelling
- Excellent durability in high service areas

Limitations

- Should not be applied if temperatures are below 10°C or when it is liable to drop below 10°C during drying period
- Dry time may be impeded if the relative humidity is high
- When painting doors and trim, Aalto WB Enamel in a satin finish or higher should be used
- Not recommended for bathrooms or wet area walls
- After applying Aalto WB Interior Enamel Flat, allow 12-48 hours before the area becomes fully serviceable

Health & Safety

For detailed health and safety information refer to material safety data sheet (MSDS).

Usage

- Provide adequate ventilation during use
- Keep out of reach of children

Personal

- Avoid contact with skin and eyes
- Wash hands after use

Protective Equipment

- Wear eye protection and waterproof gloves
- When spraying, wear dust mask or suitable respirator

Storage

- Store away from direct sunlight

Health Effects

If poisoning occurs, contact a Doctor or Poisons Information Centre (NZ 0800 764 766).

Swallowed: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water.

Eyes: If in eyes, hold eyes open, flush with running water for at least 15 minutes.

Skin: If skin contact occurs, remove contaminated clothing and wash skin thoroughly.

Inhaled: Remove from contaminated area.

Spills & Disposal

Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Do not pour leftover paint down the drain.

Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local Council regarding the disposal of empty paint containers. Empty paint containers should be left open in a well-ventilated area to dry out. When dry, recycle steel containers via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may vary between local authorities.