

aaltopaint

WB Trade Interior Ceiling Flat

Product Line Aalto WB Trade Interior Ceiling Flat
AT325

Description Aalto WB Trade Interior Ceiling Flat is a professional quality waterbased paint in an ultra flat finish (less than 1% gloss) for interior ceilings. Formulated to provide excellent opacity with an even, dead flat finish and is suitable for spraying, rolling and brushing with minimal roller splatter.

Guarantee Aalto WB Trade Interior Ceiling Flat comes with a 10 year guarantee. For details, visit www.aaltopaint.co.nz

Typical Uses May be used on suitably prepared:

- Gib® board
- Wallboard
- Timber
- Pinex
- Fibrolite
- Hardiflex
- Customwood

Properties

Binder type	Acrylic copolymer
Solvent	Water
Colour	White and tinted colours
Finish	Low sheen: < 1% gloss
Dry time	30 minutes at 20°C
Recoat time	2 hours at 20°C
Number of coats	2
Theoretical coverage	10-12m ² per litre
Recommended film thickness	100 microns per coat WFT
Thinning/clean up	Water

Preparation	Ensure surfaces are free from loose and flaking paint. Wash surfaces with a suitable cleaner such as sugar soap prior to painting to remove any oil, grease, dirt or other contaminants. Where there are areas of mould, treat with a mould remover.
Application	<p>Aalto WB Trade Interior Ceiling Flat may be applied by synthetic brush, roller or spray. Airless spray – a 415 or 515 tip is recommended. Rolling – a synthetic 8mm nap roller sleeve is recommended.</p> <p>Gib® Board, Wallboard, Pinex</p> <ol style="list-style-type: none">1. Apply 1 coat of Aalto WB Trade Sealer Undercoat, allow 2 hours to dry2. Apply 2 coats of Aalto WB Trade Interior Ceiling Flat, allowing 2 hours between coats <p>Timber, Fibrolite, Hardiflex, Customwood</p> <ol style="list-style-type: none">1. Apply 1 coat of Aalto WB Trade 3 in 1 Undercoat2. Apply 2 coats of Aalto WB Trade Interior Ceiling Flat, allowing 2 hours between coats
Performance & Limitations	<p>Performance</p> <ul style="list-style-type: none">• Excellent coverage and opacity• Easy to apply• Dries to an even dead flat finish <p>Limitations</p> <ul style="list-style-type: none">• Should not be applied if temperatures are below 10°C or when it is liable to drop below 10°C during drying period• Dry time may be impeded if the relative humidity is high
Health & Safety	<p>For detailed health and safety information refer to material safety data sheet (MSDS).</p> <p>Usage</p> <ul style="list-style-type: none">• Provide adequate ventilation during use• Keep out of reach of children <p>Personal</p> <ul style="list-style-type: none">• Avoid contact with skin and eyes• Wash hands after use <p>Protective Equipment</p> <ul style="list-style-type: none">• Wear eye protection and waterproof gloves• When spraying, wear dust mask or suitable respirator <p>Storage</p> <ul style="list-style-type: none">• Store away from direct sunlight
Health Effects	If poisoning occurs, contact a Doctor or Poisons Information Centre (NZ 0800 764 766).

Swallowed: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water.

Eyes: If in eyes, hold eyes open, flush with running water for at least 15 minutes.

Skin: If skin contact occurs, remove contaminated clothing and wash skin thoroughly.

Inhaled: Remove from contaminated area.

Spills & Disposal

Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Do not pour leftover paint down the drain.

Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local Council regarding the disposal of empty paint containers. Empty paint containers should be left open in a well-ventilated area to dry out. When dry, recycle steel containers via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may vary between local authorities.