

aaltopaint

WB Trade Undercoat Easy Sand Sealer

Product Line Aalto WB Trade Easy Sand Sealer
AT365

Description Aalto WB Trade Easy Sand Sealer is a professional quality waterbased sealer undercoat for interior broadwall surfaces. Formulated to provide a smooth, even finish with easy sand properties and excellent opacity.

Guarantee Aalto WB Trade Easy Sand Sealer comes with a 10 year guarantee. For details, visit www.aaltopaint.co.nz

Typical Uses May be used on suitably prepared interior surfaces:

- Gib® board
- Previously painted surfaces
- Composite boards
- Plaster
- Gib® board
- Timber

Properties

Binder type	Copolymer acrylic
Solvent	Water
Colour	White
Finish	Matt
Dry time	30 minutes at 20°C
Recoat time	2 hours at 20°C
Number of coats	1
Theoretical coverage	8-10m ² per litre
Recommended film thickness	100 microns per coat WFT
Thinning/clean up	Water

Preparation Ensure surfaces are free from loose and flaking paint. Wash surfaces with a suitable interior or exterior cleaner prior to painting to remove any oil, grease, dirt, mould or other contaminants.

Application Aalto WB Easy Sand Sealer may be applied by synthetic brush, roller or spray. Airless spray – a 417 or 517 tip is recommended.

Note: when applying over a substrate that has distinctly contrasting colours, tint Aalto WB Trade Easy Sand Sealer to a light grey to ensure good hiding power for the topcoats.

All Substrates

1. Apply 1 coat of Aalto WB Trade Easy Sand Sealer
2. Lightly sand and dust off well

Note: Ensure all sanding dust is removed to ensure adhesion of the topcoat

3. Apply 2 coats of selected topcoat

Performance & Limitations

Performance

- Excellent spray application
- Free sanding to a smooth surface
- Excellent holdout for topcoats

Limitations

- Do not apply if temperatures are below 10°C
- Dry time may be impeded if relative humidity is high
- For improved adhesion to timber substrates, we recommend Aalto 3 in 1 Undercoat

Health & Safety

For detailed health and safety information refer to material safety data sheet (MSDS).

Usage

- Provide adequate ventilation during use
- Keep out of reach of children

Personal

- Avoid contact with skin and eyes
- Wash hands after use

Protective Equipment

- Wear eye protection and waterproof gloves
- When spraying, wear dust mask or suitable respirator

Storage

- Store away from direct sunlight

Health Effects

If poisoning occurs, contact a Doctor or Poisons Information Centre (NZ 0800 764 766).

Swallowed: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water.

Eyes: If in eyes, hold eyes open, flush with running water for at least 15 minutes.

Skin: If skin contact occurs, remove contaminated clothing and wash skin thoroughly.

Inhaled: Remove from contaminated area.

Spills & Disposal

Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local Council regarding the disposal of empty paint containers. Empty paint containers should be left open in a well-ventilated area to dry out. When dry, recycle steel containers via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may vary between local authorities.