

aaltopaint

WB Trade Undercoat Interior Sealer Undercoat

Product Line	Aalto WB Trade Interior Sealer Undercoat AT366
Description	Aalto WB Trade Interior Sealer Undercoat is a professional quality waterbased high build sealer and undercoat for interior broadwall surfaces. Formulated to dry fast to a free sanding film with excellent opacity and holdout for topcoats.
Guarantee	Aalto WB Trade Interior Sealer Undercoat comes with a 10 year guarantee. For details, visit www.aaltopaint.co.nz
Typical Uses	May be used on suitably prepared: <ul style="list-style-type: none">• Timber• Previously painted surfaces• Composite boards• Plaster• Fibre cement• Gib® board• Wallpaper

Properties

Binder type	Copolymer acrylic
Solvent	Water
Colour	White
Finish	Matt
Dry time	30 minutes at 20°C
Recoat time	2 hours at 20°C
Number of coats	1
Theoretical coverage	8-10m ² per litre
Recommended film thickness	100 microns per coat WFT
Thinning/clean up	Water

Preparation

Ensure surfaces are free from loose and flaking paint. Wash surfaces with a suitable interior or exterior cleaner prior to painting to remove any oil, grease, dirt, mould or other contaminants.

Application

Aalto WB Trade Interior Sealer Undercoat may be applied by synthetic brush, roller or spray.
Airless spray – a 417 or 517 tip is recommended.

Note: when applying over a substrate that has distinctly contrasting colours, tint Aalto WB Trade Interior Sealer Undercoat to a light grey to ensure good hiding power for the topcoats.

All Substrates

1. Apply 1 coat of Aalto WB Trade Interior Sealer Undercoats
2. Lightly sand and dust off
3. Apply 2 coats of selected topcoat

Performance & Limitations

Performance

- Excellent spray application
- Free sanding to a smooth surface
- Excellent holdout for topcoats

Limitations

- Do not apply if temperatures are below 10°C
- Dry time may be impeded if relative humidity is high

Health & Safety

For detailed health and safety information refer to material safety data sheet (MSDS).

Usage

- Provide adequate ventilation during use
- Keep out of reach of children

Personal

- Avoid contact with skin and eyes
- Wash hands after use

Protective Equipment

- Wear eye protection and waterproof gloves
- When spraying, wear dust mask or suitable respirator

Storage

- Store away from direct sunlight

Health Effects

If poisoning occurs, contact a Doctor or Poisons Information Centre (NZ 0800 764 766).

Swallowed: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water.

Eyes: If in eyes, hold eyes open, flush with running water for at least 15 minutes.

Skin: If skin contact occurs, remove contaminated clothing and wash skin thoroughly.

Inhaled: Remove from contaminated area.

Spills & Disposal

Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local Council regarding the disposal of empty paint containers. Empty paint containers should be left open in a well-ventilated area to dry out. When dry, recycle steel containers via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may vary between local authorities.