

# Procoat Oil Based Primer Undercoat

Product	Procoat Oil Based Primer Undercoat PR380	
Description	Procoat Oil Based Primer Undercoat is a premium all purpose primer undercoat for interior and exterior applications. Formulated to be quick drying to an easy to sand surface, it is ideal as a first coat on bare timber, customwood, and plywood.	
Typical Uses	May be used on suitably prepared: <ul style="list-style-type: none"> <li>- Weatherboards</li> <li>- Timber</li> <li>- Old painted surfaces</li> <li>- Customwood and plywood</li> <li>- Suitably prepared metals</li> </ul>	
Physical Properties	Binder type Solvent Colour Finish Dry time Recoat time Number of coats Theoretical coverage Rec. film thickness Thinning and clean up	Alkyd resin Mineral turpentine White Matt 4 hours at 20°C 16 hours at 20°C 1 10-12m <sup>2</sup> per litre per coat 80 microns per coat, WFT Mineral turpentine
Preparation	Ensure surfaces are free from loose and flaking paint. Wash surfaces with a suitable cleaner such as sugar soap prior to painting to remove any oil, grease, dirt or other contaminants. Where there has been mould, treat with a mould remover.	
Application	Procoat Oil Based Primer Undercoat may be applied by brush, roller or spray. Airless spray – a 415 or 515 tip is recommended.	
Performance	All surfaces <ol style="list-style-type: none"> <li>1. Apply 1 coat of Procoat Oil Based Primer Undercoat and allow to dry overnight</li> <li>2. Sand and thoroughly dust off to a smooth finish</li> <li>3. Apply 2 coats of selected topcoat</li> </ol>	
Limitations	<ul style="list-style-type: none"> <li>- Provides excellent holdout for enamel topcoats</li> <li>- Good flow and sanding properties</li> <li>- Excellent adhesion</li> </ul>	
Limitations	<ul style="list-style-type: none"> <li>- Not recommended for cementitious substrates</li> <li>- Needs to be overcoated within 4 weeks</li> <li>- Poor alkali resistance</li> </ul>	



**Health and Safety** For detailed health and safety information refer to Material Safety Datasheet (MSDS)

**Usage**

- Provide adequate ventilation during use
- Keep out of reach of children

**Personal**

- Avoid contact with skin and eyes
- Wash hands after use

**Protective equipment**

- Wear protective eyewear and waterproof gloves
- When spraying, wear dust mask or suitable respirator

**Storage**

- Store away from direct sunlight

**Health Effects**

If poisoning occurs, contact a doctor or Poisons Information Centre (NZ 0800 764 766).

If swallowed: Rinse mouth with water. Do NOT induce vomiting. Give a glass of water.

Eyes: If in eyes, hold eyes open, flush with running water for at least 15 minutes,

Skin: If skin contact occurs, remove contaminated clothing and wash skin thoroughly.

Inhaled: Remove from contaminated area.

**Spills and Disposal**

Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local council regarding the disposal of empty paint containers. Empty paint containers should be left open in a well-ventilated area to dry out. When dry, recycle steel containers via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may vary between local authorities.