

Procoat Oil Based Pigmented Sealer

Product	Procoat Oil Based Pigmented Sealer PR384	
Description	Procoat Oil Based Pigmented Sealer is a premium quality sealer designed for application on porous and loosely bound surfaces. Formulated to seal nicotine and/or water stained walls prior to painting, and as a broadwall sealer prior to wallpapering. Also ideal for use as a joinery sealer.	
Typical Uses	May be used on suitably prepared: <ul style="list-style-type: none"> - Gib® board - Pinex - Fibrous plaster - As a wallboard sealer (prior to wallpapering) - Brick and cementitious surfaces - Timber 	
Physical Properties	Binder type	Urethane modified alkyd resin
	Solvent	Mineral turpentine
	Colour	White
	Finish	Satin
	Dry time	4 hours at 20°C
	Recoat time	16 hours at 20°C
	Number of coats	1
	Theoretical coverage	8-10m ² per litre per coat
	Rec. film thickness	80 microns per coat, WFT
	Thinning and clean up	Mineral turpentine
Preparation	Ensure surfaces are free from loose and flaking paint. Wash surfaces with a suitable cleaner such as sugar soap prior to painting to remove any oil, grease, dirt or other contaminants. Where there has been mould, treat with a mould remover.	
Application	Procoat Oil Based Pigmented Sealer may be applied by brush, roller or spray. Airless spray – a 415 or 515 tip is recommended. All surfaces <ol style="list-style-type: none"> 1. Carefully sand to a smooth, even surface and dust off thoroughly 2. Apply 1 coat of Procoat Oil Based Pigmented Sealer, allow to dry overnight 3. Apply 2 coats of selected topcoat 	
Performance	<ul style="list-style-type: none"> - Excellent adhesion to alkyd and acrylic topcoats - Easy to apply 	
Limitations	<ul style="list-style-type: none"> - As a sealer, Procoat Oil Based Pigmented Sealer is not designed to impart opacity - Contains solvent 	



Health and Safety For detailed health and safety information refer to Material Safety Datasheet (MSDS)

Usage

- Provide adequate ventilation during use
- Keep out of reach of children

Personal

- Avoid contact with skin and eyes
- Wash hands after use

Protective equipment

- Wear protective eyewear and waterproof gloves
- When spraying, wear dust mask or suitable respirator

Storage

- Store away from direct sunlight

Health Effects

If poisoning occurs, contact a doctor or Poisons Information Centre (NZ 0800 764 766).

If swallowed: Rinse mouth with water. Do NOT induce vomiting. Give a glass of water.

Eyes: If in eyes, hold eyes open, flush with running water for at least 15 minutes,

Skin: If skin contact occurs, remove contaminated clothing and wash skin thoroughly.

Inhaled: Remove from contaminated area.

Spills and Disposal

Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local council regarding the disposal of empty paint containers. Empty paint containers should be left open in a well-ventilated area to dry out. When dry, recycle steel containers via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may vary between local authorities.