

Procoat Deck and Exterior Oil Stain WB

Product	Procoat Deck and Exterior Oil Stain WB PR405	
Description	Procoat Deck and Exterior Oil Stain WB is a premium linseed oil modified stain giving you the benefits of an oil stain with the convenience of a waterbased formula. It provides colour, protection and enhancement to exterior timber surfaces, while allowing the natural grain to show through.	
Typical Uses	Ideal for all exterior timber, including: <ul style="list-style-type: none"> - Weatherboards - Decks - Fences - Pergolas - Timber furniture 	
Physical Properties	Binder type	Acrylic modified oil
	Solvent	Water
	Colour	Selected standard colours
	Finish	Matt, oiled-look finish
	Dry time	4 hours at 20°C (may take longer to become tack-free)
	Recoat time	16 hours at 20°C
	Number of coats	1-2
	Theoretical coverage	Up to 12m ² per litre per coat, depending on timber
	Thinning and clean up	Water
Preparation	<p>Ensure the surface is in sound condition, dry, and free from dirt, dust and other contaminants. Oils and grease must be removed with a suitable cleaner. Where there has been mould, treat the area with a moss and mould remover. Treat old weathered timber with Procoat Timber Cleaner & Brightener to remove dead wood fibres and discolouration.</p> <p>Stir well during use and during use with a broad flat paddle, using an up and down scooping motion.</p> <p>If multiple tins of stain are being used, we recommend mixing them all together to ensure a consistent colour.</p> <p>Do not apply to new dressed timber or timber that is damp. Allow timber to fully dry and weather before staining.</p> <p>Any timber showing signs of mill glaze should be sanded to improve penetration.</p>	
Application	<p>Procoat Deck and Exterior Oil Stain WB may be applied by brush or applicator pad. Consult your local paint specialist for recommendations.</p> <p>Bare timber</p> <ol style="list-style-type: none"> 1. Apply 1 coat of Deck and Exterior Oil Stain WB, ensuring it is worked well into the timber 2. A second coat may be required on rough sawn timbers <p>Previously stained surfaces</p> <ol style="list-style-type: none"> 1. Wash well with Procoat Deck and Exterior House Wash and treat as above 2. Apply 1 coat of Procoat Deck and Exterior Oil Stain WB, ensuring it is worked well into the timber 	



The logo for Procoat, featuring the word "procoat" in a bold, lowercase, sans-serif font. A horizontal line is positioned above the letter "o", extending from the start of the "p" to the end of the "o".

Note: Excessive coats will cause a varnished look and may lead to early failure of the stain. When restaining, always check the absorbency of the substrate, if the stain doesn't penetrate, sand back to bare timber.

Maintenance

All new work should have a second application of stain applied after the first summer to allow the timber and stain to weather in.

Wash regularly with Procoat Deck and Exterior House Wash to remove dirt build up and increase longevity of the stain.

Performance and Limitations

Performance

- Adds colour and enhances the timbers natural grain
- Waterbased for easy application and clean up
- Enriched with linseed oil for improved penetration into timber
- UV blocking pigments protect the timber from damage
- Protects against mould and algae growth
- Made in NZ specifically for NZ conditions

Limitations

- Not to be used over any surface that has been previously painted
- Should not be applied if temperatures are below 10°C or when it is liable to drop below 10°C during the drying period
- Stop staining 4 hours before dew fall, or if rain looks likely
- Stain may darken or change colour progressively as timber weathers

Health and Safety

For detailed health and safety information refer to Material Safety Datasheet (MSDS)

Usage

- Provide adequate ventilation during use
- Keep out of reach of children

Personal

- Avoid contact with skin and eyes
- Wash hands after use

Protective equipment

- Wear protective eyewear and waterproof gloves
- When spraying, wear dust mask or suitable respirator

Storage

- Store away from direct sunlight

Health Effects

If poisoning occurs, contact a doctor or Poisons Information Centre (NZ 0800 764 766).

If swallowed: Rinse mouth with water. Do NOT induce vomiting. Give a glass of water.

Eyes: If in eyes, hold eyes open, flush with running water for at least 15 minutes,

Skin: If skin contact occurs, remove contaminated clothing and wash skin thoroughly.

Inhaled: Remove from contaminated area.

Spills and Disposal

Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local council regarding the disposal of empty paint containers. Empty paint containers should be left open in a well-ventilated area to dry out. When dry, recycle steel containers via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may vary between local authorities.

The logo for Procoat, featuring the word "procoat" in a bold, lowercase, sans-serif font. A horizontal line is positioned above the "o" and "c", extending from the "p" to the "t".