

Procoat Exterior House and Deck Wash

Product	Procoat Exterior House and Deck Wash PR412
Description	<p>Procoat Exterior House and Deck Wash is a specially formulated cleaner designed to safely clean and maintain the exterior of your home. Ideal for use on exterior painted, stained and oiled surfaces prior to recoating, or as a maintenance wash to clean your surfaces and extend the life of your coating.</p> <p>The unique formulation contains a blend of biodegradable surfactants designed to easily remove dirt and grime, and help reduce the growth of moss, mould and lichen.</p>
Active Ingredients	Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides
Dilution	For general cleaning dilute 1 part cleaner with 4 parts water. Areas which have high levels of build up dilute 1 part cleaner with 1 part water.
Application	<p>Remove all surface dirt with a broom or brush. Wet the surface with water before applying. Apply the cleaner to the surface using a soft broom or brush, ensuring the surface is soaked and covered. Rinse off after 5 minutes, before the surface dries. When cleaning large areas, it is recommended to work in sections to ensure the cleaner doesn't dry out.</p> <p>Allow timber to dry thoroughly before painting, staining or oiling.</p>
Important	<p>Avoid contact with delicate vegetation. If contact occurs, rinse well with water.</p> <p>If using to clean a roof where potable water is collected, disconnect all downpipes from water tanks before cleaning. Do not reconnect until after several periods of rain to ensure any remaining product is washed away.</p>
Maintenance	We recommend washing exterior surfaces at least every 12 months.
Health and Safety	<p>For detailed health and safety information refer to Material Safety Datasheet (MSDS)</p> <p>Usage</p> <ul style="list-style-type: none"> - Provide adequate ventilation during use - Keep out of reach of children <p>Personal</p> <ul style="list-style-type: none"> - Avoid contact with skin and eyes - Wash hands after use <p>Protective equipment</p> <ul style="list-style-type: none"> - Wear protective eyewear and waterproof gloves - When spraying, wear dust mask or suitable respirator <p>Storage</p> <ul style="list-style-type: none"> - Store away from direct sunlight - Store in locked up



Health Effects

If poisoning occurs, contact a doctor or Poisons Information Centre (NZ 0800 764 766).
If swallowed: Rinse mouth with water. Do NOT induce vomiting. Give a glass of water.
Eyes: If in eyes, hold eyes open, flush with running water for at least 15 minutes,
Skin: If skin contact occurs, remove contaminated clothing and wash skin thoroughly.
Inhaled: Remove from contaminated area.

Spills and Disposal

Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local council regarding the disposal of empty paint containers. Empty paint containers should be left open in a well-ventilated area to dry out. When dry, recycle steel containers via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may vary between local authorities.

The logo for Procoat, featuring the word "procoat" in a bold, lowercase, sans-serif font. A horizontal line is positioned above the "o" and "c" in "coat", extending from the "p" to the end of the "t".