

Procoat Universal

Product	Procoat Universal PR425	
Description	Procoat Universal is a multi-purpose, self priming acrylic paint for use on all common exterior substrates including timber, weatherboards, galvanised iron and concrete. Enhanced with linseed oil to improve penetration, Procoat Universal is ideal for fences, pergolas, farm buildings, sheds, garages and more.	
Typical Uses	May be used on suitably prepared: <ul style="list-style-type: none"> - Timber - Fibre cement sheet - Weatherboards - Concrete blocks and brickwork 	
Physical Properties	Binder type	100% acrylic
	Solvent	Water
	Colour	White and selected standard colours
	Finish	Low sheen – 15% gloss
	Dry time	30 minutes at 20°C
	Recoat time	2 hours at 20°C
	Number of coats	2
	Theoretical coverage	10-12m ² per litre per coat
	Rec. film thickness	100 microns per coat, WFT
	Thinning and clean up	Water
Preparation	Ensure surfaces are free from loose and flaking paint. Wash surfaces with a suitable cleaner such as sugar soap prior to painting to remove any oil, grease, dirt or other contaminants. Where there are areas of mould, treat with a mould remover.	
Application	Procoat Universal may be applied by synthetic brush, roller, or spray. Consult your local paint specialist for recommendations. Apply 2 coats of Procoat Universal to the substrate, allowing at least 2 hours between coats.	
Performance	<ul style="list-style-type: none"> - Excellent durability - Excellent intercoat adhesion - Excellent flexibility - Resists dirt pickup - Suitable for the collection of potable water 	
Limitations	<ul style="list-style-type: none"> - Dry time may be impeded if the relative humidity is high - Should not be applied if temperatures are below 5°C or when it is liable to drop below 5°C during the drying period - Stop painting 4 hours before dew fall, or if rain looks likely - Should not be used on closing surfaces, such as around doors or windows - When applying light colours over tannin rich timbers like cedar, use an oil based undercoat to prevent tannin bleed 	

Health and Safety For detailed health and safety information refer to Material Safety Datasheet (MSDS)

Usage

- Provide adequate ventilation during use
- Keep out of reach of children

Personal

- Avoid contact with skin and eyes
- Wash hands after use

Protective equipment

- Wear protective eyewear and waterproof gloves
- When spraying, wear dust mask or suitable respirator

Storage

- Store away from direct sunlight

Health Effects

If poisoning occurs, contact a doctor or Poisons Information Centre (NZ 0800 764 766).

If swallowed: Rinse mouth with water. Do NOT induce vomiting. Give a glass of water.

Eyes: If in eyes, hold eyes open, flush with running water for at least 15 minutes,

Skin: If skin contact occurs, remove contaminated clothing and wash skin thoroughly.

Inhaled: Remove from contaminated area.

Spills and Disposal

Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local council regarding the disposal of empty paint containers. Empty paint containers should be left open in a well-ventilated area to dry out. When dry, recycle steel containers via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may vary between local authorities.