

Procoat Fence Paint

Product	Procoat Fence Paint PR435	
Description	Procoat Fence Paint is a 100% acrylic fence paint for use on exterior bare timber fences. It provides great coverage and an even, low sheen finish.	
Typical Uses	May be used on suitably prepared: <ul style="list-style-type: none"> - Bare, rough sawn timber fences - Post and rail fences 	
Physical Properties	Binder type	100% acrylic
	Solvent	Water
	Colour	Range of standard colours
	Finish	Low sheen
	Dry time	40 minutes at 20°C
	Recoat time	2-4 hours at 20°C
	Number of coats	2
	Theoretical coverage	6-10m ² per litre per coat
	Thinning and clean up	Water
Preparation	<p>Ensure surfaces are free from loose and flaking paint. Wash surfaces with a suitable cleaner such as sugar soap prior to painting to remove any oil, grease, dirt or other contaminants. Where there are areas of mould, treat with a mould remover.</p> <p>Bare timber must be adequately dry before painting. Wet timber will cause decreased product penetration and adhesion, and lessen the life of the coating.</p> <p>New LOSP treated timber should be left for 14 days before painting.</p>	
Application	<p>Procoat Universal may be applied by synthetic brush, roller, or spray. Consult your local paint specialist for recommendations.</p> <p>Stir well before use.</p> <p>Apply 2 coats of Procoat Fence Paint to the substrate, allowing 2-4 hours between coats.</p>	
Performance	<ul style="list-style-type: none"> - Great durability on suitably prepared timber - Easy to apply 	
Limitations	<ul style="list-style-type: none"> - Coverage may be reduced on previously painted surfaces - Should not be applied if temperatures are below 10°C or when it is liable to drop below 10°C during the drying period 	
Health and Safety	<p>For detailed health and safety information refer to Material Safety Datasheet (MSDS)</p> <p>Usage</p> <ul style="list-style-type: none"> - Provide adequate ventilation during use - Keep out of reach of children 	

Personal

- Avoid contact with skin and eyes
- Wash hands after use

Protective equipment

- Wear protective eyewear and waterproof gloves
- When spraying, wear dust mask or suitable respirator

Storage

- Store away from direct sunlight

Health Effects

If poisoning occurs, contact a doctor or Poisons Information Centre (NZ 0800 764 766).

If swallowed: Rinse mouth with water. Do NOT induce vomiting. Give a glass of water.

Eyes: If in eyes, hold eyes open, flush with running water for at least 15 minutes,

Skin: If skin contact occurs, remove contaminated clothing and wash skin thoroughly.

Inhaled: Remove from contaminated area.

Spills and Disposal

Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local council regarding the disposal of empty paint containers. Empty paint containers should be left open in a well-ventilated area to dry out. When dry, recycle steel containers via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may vary between local authorities.

The logo for Procoat, featuring the word "procoat" in a bold, lowercase, sans-serif font. A horizontal line is positioned above the "o" and "c", extending from the "p" to the "t".